


MOOD DOWNLIGHT

Φ55 Adjustable Round



Adjustable Optic



baffle



Black Matt



White Matt



Silver Matt



Grey Specular



Black Specular



Silver Specular




Gold Specular




Bespoke

IP Rating:	IP20 and IP44 options
Optics:	10°/24°/36°/50°
UGR:	<10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K
Typical Source	
Efficacy (lm/W):	
Control:	110
Binning:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Input:	2 Step MacAdams
Output:	AC220-240V 50/60Hz DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 °C to 45 °C
Class:	II
Optional accessories:	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter




10W Ra98 3000K 10°

h(m)	E(lx)	D(m)
0.5	8431	0.11
1.0	2108	0.21
1.5	937	0.32
2.0	527	0.43
2.5	337	0.53
3.0	234	0.64



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	4847	0.21
1.0	1212	0.43
1.5	539	0.64
2.0	303	0.86
2.5	194	1.07
3.0	135	1.29




10W Ra98 3000K 36°


h(m)	E(lx)	D(m)
0.5	2553	0.32
1.0	638	0.65
1.5	284	0.97
2.0	160	1.29
2.5	102	1.61
3.0	71	1.94




DuraGreen project:
Hilton Hotel



W system	lm system	optics	code
6W	328	10°	AFL5506W-30N10-W
6W	407	24°	AFL5506W-30N24-W
6W	417	36°	AFL5506W-30N36-W
6W	411	50°	AFL5506W-30N50-W



W system	lm system	optics	code
8W	384	10°	AFL5508W-30N10-W
8W	501	24°	AFL5508W-30N24-W
8W	517	36°	AFL5508W-30N36-W
8W	513	50°	AFL5508W-30N50-W



W system	lm system	optics	code
10W	411	10°	AFL5510W-30N10-W
10W	554	24°	AFL5510W-30N24-W
10W	567	36°	AFL5510W-30N36-W
10W	559	50°	AFL5510W-30N50-W