


MOOD DOWNLIGHT

Φ75

Trimless Adjustable Round



Adjustable Optic



baffle



Black Matt



White Matt



Silver Matt



Grey Specular



Black Specular



Silver Specular



Gold Specular




Bespoke

- IP Rating:**
Optics:
UGR:
CRI:
Lifetime:
CCT:

IP20 and IP44 options
5°/10°/24°/36°/50°
<10
98Ra
>50,000 hrs (L70 B10)
2700K/3000K/3500K/4000K/5000K/
2000K-3000K/1800K-4000K/2700K-6000K
- Typical Source**
Efficacy (lm/W):
Control:
Binning:
Input:
Output:


110
On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
2 Step MacAdams
AC220-240V 50/60Hz
DC 3V 650mA 3W
DC 36V 200mA 8W
DC 36V 250mA 10W
DC 36V 300mA 12W
DC 36V 350mA 15W
- Ambient temp:**
Class:
Optional accessories:

-20 °C to 45 °C
II
Honeycomb louvre, Solite Lense, Spread Lense,
Colour Filter




15W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	19856	0.12
1.0	4964	0.23
1.5	2206	0.35
2.0	1241	0.46
2.5	794	0.58
3.0	552	0.69




15W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	9636	0.20
1.0	2409	0.41
1.5	1071	0.61
2.0	602	0.81
2.5	385	1.02
3.0	268	1.22



15W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	5780	0.30
1.0	1445	0.60
1.5	642	0.89
2.0	361	1.19
2.5	231	1.49
3.0	161	1.79



15W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	2268	0.46
1.0	567	0.92
1.5	252	1.37
2.0	142	1.83
2.5	91	2.29
3.0	63	2.75



DuraGreen project:
Poliform Showroom

W system	lm system	optics	code
3W	152	5°	AFL7503W-TL-30N05-W

W system	lm system	optics	code
8W	415	10°	AFL7508W-TL-30N10-W
8W	535	15°	AFL7508W-TL-30N15-W
8W	598	24°	AFL7508W-TL-30N24-W
8W	632	36°	AFL7508W-TL-30N36-W
8W	573	50°	AFL7508W-TL-30N50-W

W system	lm system	optics	code
10W	450	10°	AFL7510W-TL-30N10-W
10W	590	15°	AFL7510W-TL-30N15-W
10W	618	24°	AFL7510W-TL-30N24-W
10W	699	36°	AFL7510W-TL-30N36-W
10W	650	50°	AFL7510W-TL-30N50-W

W system	lm system	optics	code
12W	531	10°	AFL7512W-TL-30N10-W
12W	755	15°	AFL7512W-TL-30N15-W
12W	860	24°	AFL7512W-TL-30N24-W
12W	901	36°	AFL7512W-TL-30N36-W
12W	835	50°	AFL7512W-TL-30N50-W

W system	lm system	optics	code
15W	568	10°	AFL7515W-TL-30N10-W
15W	858	15°	AFL7515W-TL-30N15-W
15W	929	24°	AFL7515W-TL-30N24-W
15W	1041	36°	AFL7515W-TL-30N36-W
15W	952	50°	AFL7515W-TL-30N50-W