


MOOD DOWNLIGHT

Φ75 Adjustable Round




Adjustable Optic



baffle




- IP Rating:** IP20 and IP44 options
- Optics:** 5°/10°/15°/24°/36°/50°
- UGR:** <10
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K/5000K/
2000K-3000K/1800K-4000K/2700K-6000K
- Typical Source**
- Efficacy (lm/W):** 110
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 3V 650mA 3W
DC 36V 200mA 8W
DC 36V 250mA 10W
DC 36V 300mA 12W
DC 36V 350mA 15W
- Ambient temp:** -20 °C to 45 °C
- Class:** II
- Optional accessories:** Honeycomb louvre, Solite Lense, Spread Lense,
Colour Filter




15W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	19856	0.12
1.0	4964	0.23
1.5	2206	0.35
2.0	1241	0.46
2.5	794	0.58
3.0	552	0.69




15W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	9636	0.20
1.0	2409	0.41
1.5	1071	0.61
2.0	602	0.81
2.5	385	1.02
3.0	268	1.22



15W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	5780	0.30
1.0	1445	0.60
1.5	642	0.89
2.0	361	1.19
2.5	231	1.49
3.0	161	1.79




15W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	2268	0.46
1.0	567	0.92
1.5	252	1.37
2.0	142	1.83
2.5	91	2.29
3.0	63	2.75




DuraGreen project:
Bentley Home




W system	lm system	optics	code
3W	152	5°	AFL7503W-30N05-W




W system	lm system	optics	code
8W	415	10°	AFL7508W-30N10-W
8W	535	15°	AFL7508W-30N15-W
8W	598	24°	AFL7508W-30N24-W
8W	632	36°	AFL7508W-30N36-W
8W	573	50°	AFL7508W-30N50-W



W system	lm system	optics	code
10W	450	10°	AFL7510W-30N10-W
10W	590	15°	AFL7510W-30N15-W
10W	618	24°	AFL7510W-30N24-W
10W	699	36°	AFL7510W-30N36-W
10W	650	50°	AFL7510W-30N50-W



W system	lm system	optics	code
12W	531	10°	AFL7512W-30N10-W
12W	755	15°	AFL7512W-30N15-W
12W	860	24°	AFL7512W-30N24-W
12W	901	36°	AFL7512W-30N36-W
12W	835	50°	AFL7512W-30N50-W



W system	lm system	optics	code
15W	568	10°	AFL7515W-30N10-W
15W	858	15°	AFL7515W-30N15-W
15W	929	24°	AFL7515W-30N24-W
15W	1041	36°	AFL7515W-30N36-W
15W	952	50°	AFL7515W-30N50-W