

MOOD ZOOM


Φ75 Adjustable Round



cutout :75mm



Adjustable Optic



VARIABLE BEAM SPOT




baffle




IP Rating:	IP20 and IP44 options
Optics:	15°-50°
UGR:	<10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K

Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 250mA 10W
Ambient temp:	-20 C to 45 C
Class:	II
Optional accessories:	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter



10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	6134	0.14
1.0	1533	0.28
1.5	682	0.42
2.0	383	0.56
2.5	245	0.70
3.0	170	0.84



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	793	0.50
1.0	198	1.00
1.5	88	1.50
2.0	50	2.00
2.5	32	2.50
3.0	22	3.00



DuraGreen project:
2046 Black Pearl restaurant



W system	lm system	optics	code
10W	351-291	15°- 50°	AFZ7510W-30N1550-W