




NEONFLEX

NEON STRIP 1616 BEND TOP

flexible on the horizontal axis




BEND TOP



AP1616U



Accessories not included



Clips (AC1616U)



Rigid Profile (AP1616U)



Flexible Profile (AF1616U)

IP Rating:	IP67
Optics:	115°
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/4000K/6500K/2700K-6500K/RGBW
Typical Source Efficacy (lm/W):	113
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Voltage:	DC 24V
Power(W):	8W/m, 10W/m, 15W/m, 20W/m
Ambient temp:	-20 °C to 45 °C
Class:	III



DuraGreen project:
London Luxury Home



W system	lm system	optics	code
8W	70Lm /W	115°	E67-BT1616-08W-27
8W	70Lm /W	115°	E67-BT1616-08W-30
8W	72Lm /W	115°	E67-BT1616-08W-40
8W	72Lm /W	115°	E67-BT1616-08W-65
8W	78Lm /W	115°	E67-BT1616-08W-2765
8W	20Lm /W	115°	E67-BT1616-08W-RGBW



W system	lm system	optics	code
10W	70Lm /W	115°	E67-BT1616-10W-27
10W	70Lm /W	115°	E67-BT1616-10W-30
10W	72Lm /W	115°	E67-BT1616-10W-40
10W	72Lm /W	115°	E67-BT1616-10W-65
10W	78Lm /W	115°	E67-BT1616-10W-2765
10W	20Lm /W	115°	E67-BT1616-10W-RGBW



W system	lm system	optics	code
15W	70Lm /W	115°	E67-BT1616-15W-27
15W	70Lm /W	115°	E67-BT1616-15W-30
15W	72Lm /W	115°	E67-BT1616-15W-40
15W	72Lm /W	115°	E67-BT1616-15W-65
15W	78Lm /W	115°	E67-BT1616-15W-2765
15W	20Lm /W	115°	E67-BT1616-15W-RGBW