




NEONFLEX

NEON STRIP 1616 BEND TOP IP68

flexible on the horizontal axis




BEND TOP



AP1616U




Accessories not included



Clips (AC1616U)



Rigid Profile (AP1616U)



Flexible Profile (AF1616U)

IP Rating:	IP68
Optics:	115°
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/4000K/6500K/2700K-6500K
Typical Source	
Efficacy (lm/W):	113
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Voltage:	DC 24V
Power(W):	12W/m
Ambient temp:	-20 °C to 45 °C
Class:	III



W system	lm system	optics	code
12W	70Lm /W	115°	E68-BT1616-12W-27
12W	70Lm /W	115°	E68-BT1616-12W-30
12W	72Lm /W	115°	E68-BT1616-12W-40
12W	72Lm /W	115°	E68-BT1616-12W-65
12W	78Lm /W	115°	E68-BT1616-12W-2765



W system	lm system	optics	code
R=4W	10Lm/W	115°	E68-BT1616-12W-RGBW
G=4W	26Lm/W		
B=4W	5Lm/W		
W=4W	35Lm/W		