

# ACME CURVE



## Φ78 Engine Curve Mini-Trim Adjustable Round Downlight



cutout:78mm



Adjustable Optic



91

Ø84



Standard

Black Painted  
9005

White Painted  
9016

Curated Finishes (MOQ 20 applies)

Polished Brass Black Nickel

Bright Chrome Dark Brass

|                   |                                                                       |
|-------------------|-----------------------------------------------------------------------|
| <b>IP Rating:</b> | IP20 and IP44 options                                                 |
| <b>Optics:</b>    | 15°/24°/36°/50°                                                       |
| <b>UGR:</b>       | < 10                                                                  |
| <b>CRI:</b>       | 98Ra                                                                  |
| <b>Lifetime:</b>  | >50,000 hrs (L70 B10)                                                 |
| <b>CCT:</b>       | 2700K/3000K/3500K/4000K/5000K/<br>2000K-3000K/1800K-4000K/2700K-6000K |

|                         |                                                         |
|-------------------------|---------------------------------------------------------|
| <b>Typical Source</b>   |                                                         |
| <b>Efficacy (lm/W):</b> | 110                                                     |
| <b>Control:</b>         | On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi       |
| <b>Binning</b>          | 2 Step MacAdams                                         |
| <b>Input:</b>           | AC220-240V 50/60Hz                                      |
| <b>Output:</b>          | DC 36V 200mA 8W<br>DC 36V 250mA 10W<br>DC 36V 300mA 12W |

**Ambient temp:** -20 °C to 45 °C


**Class:** II

**Optional accessories:** Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter

**Ceiling Thickness:** 9mm-28mm


**Material:** Fine aluminium 6063A

**Fire resistance test:** 60 minutes




12W Ra98 3000K 15°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 0.5  | 18360 | 0.13 |
| 1.0  | 4590  | 0.26 |
| 1.5  | 2040  | 0.39 |
| 2.0  | 1148  | 0.52 |
| 2.5  | 734   | 0.65 |
| 3.0  | 510   | 0.78 |




12W Ra98 3000K 24°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 0.5  | 6420  | 0.22 |
| 1.0  | 1605  | 0.44 |
| 1.5  | 713   | 0.65 |
| 2.0  | 401   | 0.87 |
| 2.5  | 257   | 1.09 |
| 3.0  | 178   | 1.31 |



12W Ra98 3000K 36°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 0.5  | 2791  | 0.31 |
| 1.0  | 698   | 0.62 |
| 1.5  | 310   | 0.93 |
| 2.0  | 174   | 1.25 |
| 2.5  | 112   | 1.56 |
| 3.0  | 78    | 1.87 |



12W Ra98 3000K 50°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 0.5  | 1324  | 0.52 |
| 1.0  | 331   | 1.03 |
| 1.5  | 147   | 1.55 |
| 2.0  | 83    | 2.06 |
| 2.5  | 53    | 2.58 |
| 3.0  | 37    | 3.10 |



| W system | lm system | optics | code               |
|----------|-----------|--------|--------------------|
| 8W       | 450       | 15°    | AFL7808W-C-30N15-B |
| 8W       | 442       | 24°    | AFL7808W-C-30N24-B |
| 8W       | 397       | 36°    | AFL7808W-C-30N36-B |
| 8W       | 327       | 50°    | AFL7808W-C-30N50-B |



| W system | lm system | optics | code               |
|----------|-----------|--------|--------------------|
| 10W      | 580       | 15°    | AFL7810W-C-30N15-B |
| 10W      | 563       | 24°    | AFL7810W-C-30N24-B |
| 10W      | 519       | 36°    | AFL7810W-C-30N36-B |
| 10W      | 500       | 50°    | AFL7810W-C-30N50-B |



| W system | lm system | optics | code               |
|----------|-----------|--------|--------------------|
| 12W      | 689       | 15°    | AFL7812W-C-30N15-B |
| 12W      | 671       | 24°    | AFL7812W-C-30N24-B |
| 12W      | 618       | 36°    | AFL7812W-C-30N36-B |
| 12W      | 598       | 50°    | AFL7812W-C-30N50-B |



Black Nickel



Solid Brass



Antique Bronze



Black Painted 9005



White Painted 9016



Brushed Grey



Polished Chrome

Our light fixtures are made of the highest quality metal materials, like pure aluminium and solid brass. Our process is precise and sustainable to achieve circular products that last longer and look stylish.

The ACME light engines come in three distinct shapes: straight baffle for maximum brightness, curve baffle for a softer light effect, and semi-recessed baffle for added ceiling decoration. They are available in five different sizes with both trimmed and trimless bezels (cutouts of 50mm, 57mm, 68mm, and 78mm) and offered in seven standard finishes including white 9016, black 9005, polished chrome, black nickel, antique bronze, and solid brass.



ACME STRAIGHT



ACME CURVE



ACME SEMI

We transform premium materials into fine luxury goods that elevate any space.



Light engine



Installation frame trimless



Installation frame trim

Circular economy principles are intricately woven into every stage of our design and manufacturing process, making ACME downlights a shining example of sustainability. These fixtures are fully modular, allowing for easy repair, reuse, and end-of-life reintroduction into standard stock.

Safety wire



Accessories

Spread



Double Asymmetric



Honeycomb



Red filter




Blue filter



Amber filter



Accessories



Light Engines



Specification Code

| Type            | Engine  | Power | Colour Temp      | Driver      | Beam Width   | Bezel Colour       | Baffle Colour      | Options        |
|-----------------|---------|-------|------------------|-------------|--------------|--------------------|--------------------|----------------|
| MFL             | 50      | 08W   | 30               | N           | 24           | W                  | B                  | S              |
| MFL/Fixed       | 36/36mm |       | 27/2700K         | M/Mains Dim | 10/10°       | W/White            | W/White            | H/Honeycomb    |
| AFL/Adjustable  | 50/50mm |       | 30/3000K         | D/DALI      | 15/15°       | B/Black            | B/Black            | S/Spread Lense |
| TL/Trimless     | 57/57mm |       | 35/3500K         | 0/0-10V     | 24/24°       | BG/Brushed Grey    | BG/Brushed Grey    |                |
| Q/Square        | 68/68mm |       | 40/4000K         | Z/Zigbee    | 36/36°       | BN/Black Nickel    | BN/Black Nickel    |                |
| C/ Curve        | 78/78mm |       | 50/5000K         | C/Casambi   | 50/50°       | AB/Antique Bronze  | AB/Antique Bronze  |                |
| M/Semi-Recessed |         |       | 2030/2000K-3000K | N/Non Dim   | WS/Wall Wash | SB/Solid Brass     | SB/Solid Brass     |                |
| RTP/Recessed    |         |       | 1840/1800K-4000K | X/No Driver |              | PC/Polished Chrome | PC/Polished Chrome |                |
| Pendant         |         |       | 2760/2700K-6000K |             |              |                    |                    |                |
| TLP/ Trimless   |         |       |                  |             |              |                    |                    |                |
| Pendant         |         |       |                  |             |              |                    |                    |                |
| STP/Surface     |         |       |                  |             |              |                    |                    |                |
| Pendant         |         |       |                  |             |              |                    |                    |                |
| MPW/48V Pendant |         |       |                  |             |              |                    |                    |                |