


BELLA PRO 48V


Φ41 Adjustable 48V Track Light



Adjustable Optic



minimal track



standard track

Standard



Black Painted
9005



White Painted
9016

Curated Finishes (MOQ 20 applies)



Polished Brass



Black Nickel



Bright Chrome



Rose Gold



Pearl Nickel



Antique Copper



Aged Bronze



Antique Brass




Dark Brass




Brushed Grey

IP Rating:	IP20
Optics:	15°/30°/40°/55°
UGR:	<17
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K/3500K/2700-6000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	48VDC
Output:	DC 12V 350mA 6W
Ambient temp:	-20 °C to 45 °C
Class:	III
Material:	Fine aluminium 6063A
Optional Accessories	
(fixed beam):	Honeycomb Louvre, Linear Filter
Certification :	CB/CE/UKCA/GLOBAL MARK




6W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	4391	0.14
1.0	1098	0.27
1.5	488	0.41
2.0	274	0.55
2.5	176	0.68
3.0	122	0.82




6W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	1572	0.38
1.0	393	0.76
1.5	175	1.15
2.0	98	1.53
2.5	63	1.91
3.0	44	2.29



6W Ra98 3000K 30°

h(m)	E(lx)	D(m)
0.5	2085	0.28
1.0	521	0.55
1.5	232	0.83
2.0	130	1.10
2.5	83	1.38
3.0	58	1.65



6W Ra98 3000K 55°

h(m)	E(lx)	D(m)
0.5	707	0.53
1.0	177	1.07
1.5	79	1.60
2.0	44	2.14
2.5	28	2.67
3.0	20	3.20



W system	lm system	optics	code
6W	267	15°	MT4106W-30N15-B
6W	353	30°	MT4106W-30N30-B
6W	430	40°	MT4106W-30N40-B
6W	415	55°	MT4106W-30N55-B