

BELLA PRO


Φ41 Trimless Adjustable Spotlight



cutout :36mm



Adjustable Optic



Standard

Black Painted
9005

White Painted
9016

Curated Finishes (MOQ 20 applies)

Polished Brass

Black Nickel

Bright Chrome

Rose Gold

Pearl Nickel

Antique Copper


Aged Bronze

Antique Brass

Dark Brass


Brushed Grey

IP Rating:	IP20
Optics:	15°/30°/40°/55°
UGR:	<17
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K/3500K/2700-6000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 12V 350mA 6W
Ambient temp:	-20 °C to 45 °C
Class:	II
Material:	Fine aluminium 6063A
Optional Accessories	
(fixed beam):	Honeycomb Louvre, Linear Filter
Certification :	CB/CE/UKCA/GLOBAL MARK




6W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	4391	0.14
1.0	1098	0.27
1.5	488	0.41
2.0	274	0.55
2.5	176	0.68
3.0	122	0.82




6W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	1572	0.38
1.0	393	0.76
1.5	175	1.15
2.0	98	1.53
2.5	63	1.91
3.0	44	2.29



6W Ra98 3000K 30°

h(m)	E(lx)	D(m)
0.5	2085	0.28
1.0	521	0.55
1.5	232	0.83
2.0	130	1.10
2.5	83	1.38
3.0	58	1.65



6W Ra98 3000K 55°

h(m)	E(lx)	D(m)
0.5	707	0.53
1.0	177	1.07
1.5	79	1.60
2.0	44	2.14
2.5	28	2.67
3.0	20	3.20



W system	lm system	optics	code
6W	267	15°	TL4106W-30N15
6W	353	30°	TL4106W-30N30
6W	430	40°	TL4106W-30N40
6W	415	55°	TL4106W-30N55